

EYEKANDY™ 2K URETHANE KANDY

Description

EyeKandy™ 2K combines proprietary urethane polymers with premium solvents, U.V. additives, and the true dye based candy pigments to create deep rich colors for that unique color only Kandys can exhibit. May be used with or without clear these colors are versatile and easy to use. Compared to Kandy basecoats these colors look deeper and have less bleed through on graphics applied over them. Metallics and PrismFx make great base colors for these kandys.



Components




- **EKU-600 Series.....EyeKandy™ Urethane Colors**
- **UA Series Polyurethane Activators**
- **UR Series Reducers**

Suitable Substrates



Apply over 2K urethane primer, or basecoat after proper flash times. The final color and depth of EyeKandy finishes is dependent on the color of the base chosen and the thickness of coats applied. Coarse Metallic bases and bases of PrismFx are well suited for EyeKandy as they give a deep, bright, and often 3D effect.

Mix Ratio



For spray applications mix 4 parts KemBase base with 1 part UA series urethane activator and thin with an additional 1 part UR Series urethane grade reducer by volume. Additional reduction may be required for use in an air brush application. Mix gently then strain before use.

Application



Apply 2-4 medium coats using 75% overlap at a gun distance of 6-10 inches. Guns should be equipped with 1.3-1.5 mm tips and set for 40-55 PSI for conventional guns or 8-10 PSI at the cap for HVLP. Avoid heavy or very light coats so as to ensure good orientation of the pigments. Allow to flash 10-15 minutes between coats. As a general rule the finish should be tacky but not transfer “strings” to the finger when touches between coats. After final coat application allow to flash at least 30 minutes but then apply 2K polyurethane clear for maximum protection. If not cleared immediately allow to cure over night then scuff lightly with 600-800 grit sand paper and apply 2K clear.

Read MSDS of all components before using. Use proper personal protective equipment at all times. For use by professionally trained painters. **KEEP OUT OF REACH OF CHILDREN.** Bayou Innovations, LLC warrants that its products are free from defects at time of shipping. All other warranties and guaranties of any kind whether expressed or implied are disclaimed.